

## SPECIFICATIONS

This product is a combination metal and paper wallboard cornerbead tape that is used in conjunction with a joint compound to conceal inside and outside corners. Perfect for creating corners over insulated duct work when finishing with canvas and mastic or for use with zero perm jacketing materials.

The product consist of 2" wide aluminum bonded 100% to unperforated, unsparked paper tape with moisture and alkali resistant adhesive.

### Material Metal:

1 piece 2" wide scored annealed aluminum x .016" thickness with a clean neutral surface to allow adhesion on both sides.

### Paper Tape:

Paper backing is 4½" wide.

### Packaging:

Packaged 100 ft. per roll, 5 rolls per case

### Certification:

Product conforms to ASTM B 209 standards.



### Physical Analysis

Mill Finish	.0162 gauge aluminium
Tensile strength - PSI	21,500
Yield strength - PSI	20,100
Elongation	8.5%

For more information on GLT Products, please call toll-free at 800.874.1748 or visit us online at [www.gltproducts.com](http://www.gltproducts.com).



#### HEADQUARTERS:

6810 Cochran Road | Solon, OH 44139 | 440.914.1122 | 440.914.1133 Fax | **1.800.874.1748**

#### DISTRIBUTION CENTERS:

**Ohio:** 6810 Cochran Road | Solon, OH 44139 | 440.914.1122

**Texas:** 2902 East 13th Street, Suite 200 | La Porte, TX 77571 | 713.670.9700

**North Carolina:** 501 West Camel Street | Greensboro, NC 27401 | 1.800.551.9760

**California:** 4113 Gold River Lane | Stockton, CA 95215 | 1.800.833.4500