

TECHNICAL INFO

Glass lagging fabrics are designed to replace asbestos. They are used for removable blankets, pipe wrapping, turbine blankets, fittings, flange covers and engine exhaust pipes.

Fiberglass Lagging Cloth Style 84215/9383 has been treated so that large percentages of organic binders on the fabric have been removed. This enhances the hand and weave setting characteristics. Base fabric certification - MIL 20079H, Type 1. This fabric has been designed for continuous use at temperatures up to 1000°.

Physical Specifications

Weight: 8.5 Oz. Sq. Yd.

Thickness: .018"

Tread Count: 18 x 14

Tensile Warp: 100

Tensile Fill: 45

Weave: Plain



All statements herein are expressions of opinion which we believe to be accurate and reliable but are not intended as recommendations for their use in the infringement of any patent. No patent warranty of any kind, expressed or implied is made or intended.

For more information on GLT Products, please call toll-free at 800.874.1748 or online at www.gltproducts.com.



Innovative Insulation Systems

HEADQUARTERS:

6810 Cochran Road | Solon OH 44139 | 440.914.1122 | 440.914.1133 Fax | **1.800.874.1748**

DISTRIBUTION CENTERS:

Ohio: 6810 Cochran Road | Solon OH 44139 | 440.914.1122

North Carolina: 501 West Camel Street | Greensboro, NC 27401 | 1.800.551.9760

California: 4283 Pock Lane #200 | Stockton, CA 95206 | 1.800.833.4500

Texas: 8905 Market Street | Houston, TX 77029 | 1.800.874.1748